

MBH[®] **PUMPS**

SS FAB SERIES

Suitable for Borewell Sizes of (Sheet Metal SS 304 & 316 Pumps) 4" 6" 8" 10"



ISO 9001:2008
Certified Company

A Mark of Quality

SS FAB SERIES

- Also available option are 50 hertz and 60hertz
- Also ask for casted SS pumps and motors
(suitable for long lasting and harsh climate conditions)

MATERIAL OF CONSTRUCTION

Check Valve Housing	S.S. 304
Check Valve	S.S. 304
Impeller	S.S. 304
Diffuser	S.S. 304
Pump Shell / Clump (S.S. Pump)	S.S. 304
Pump Shaft	S.S. 410 / 431
Suction inter Connector	S.S. 304
Coupling	S.S. 304

- Suitable for following pump liquids
- Clean, thin, non-aggressive, non-explosive, clear, cold, fresh water without abrasives, solid particle or fibers shall mean the water having the following characteristics.

SPECIFICATION

Temperature	33Â°C (max.)
Permissible amount of sand	25 gms / m ³ (max.)
Chlorine ion density	500 ppm (max.)
Allowable solids	3000 ppm (max.)
Specific gravity	1.004 (max.)
Hardness (drinking water)	300 ppm (max.)
Viscosity	1.75 x 10 ⁶ m ² /sec (max.)
Turbidity	50 ppm silica scale (max.)
pH value	6.5 to 8.5.



*As improvements are made in design from time to time, specifications and performance are subject to change without prior notice.
Installation photographs shown in catalogue are for illustration only.*

MBH PUMPS

mbh pumps (gujarat) pvt. ltd.

Office & Factory :
Plot No. 14, G.I.D.C. Naroda Indl. Estate,
Ahmedabad - 382 330, India.
Phone : +91-79-2282 3066, 2282 1018
E-mail : marketing@mbhpumps.com
Website : www.mbhpumps.com

Authorised Dealer :